
Flask-Blogging Documentation

Release 0.1.0

Gouthaman Balaraman

June 22, 2015

1	Quick Start Example	3
2	Configuring your Application	5
3	Blog Views	7
4	Screenshots	9
4.1	Blog Page	10
4.2	Blog Editor	10
5	API Documentation	11
5.1	Module contents	11
5.2	Submodules	11
5.3	flask_blogging.engine module	11
5.4	flask_blogging.processor module	12
5.5	flask_blogging.sqlastorage module	12
5.6	flask_blogging.storage module	14
5.7	flask_blogging.views module	15
5.8	flask_blogging.forms module	15
	Python Module Index	17

Flask-Blogging is a Flask extension for adding blog support to your site. It provides a flexible mechanism to store the data in the database of your choice. It is meant to work with the authentication provided by packages such as [Flask-Login](#) or [Flask-Security](#).

The philosophy behind this extension is to provide a lean app based on markdown to provide blog support to your existing web application. This is contrary to some other packages such as that are just blogs. If you already have a web app and you need to have a blog to communicate with your user or to promote your site through content based marketing.

Out of the box Flask-Blogging has support for the following:

- Bootstrap based site
- Markdown based blog editor
- Models to store blog
- Authentication of User's choice
- Sitemap, ATOM support
- Disqus support for comments
- Google analytics for usage tracking
- Well documented, tested, and extensible design

- [*Quick Start Example*](#)
 - [*Configuring your Application*](#)
 - [*Blog Views*](#)
 - [*Screenshots*](#)
 - [*Blog Page*](#)
 - [*Blog Editor*](#)
 - [*API Documentation*](#)
 - [*Module contents*](#)
 - [*Submodules*](#)
 - [*flask_blogging.engine module*](#)
 - [*flask_blogging.processor module*](#)
 - [*flask_blogging.sqlastorage module*](#)
 - [*flask_blogging.storage module*](#)
 - [*flask_blogging.views module*](#)
 - [*flask_blogging.forms module*](#)

Quick Start Example

```

from flask import Flask, render_template_string, redirect
from sqlalchemy import create_engine
from flask.ext.login import UserMixin, LoginManager, \
    login_user, logout_user
from flask_blogging import SQLAStorage, BloggingEngine

app = Flask(__name__)
app.config["SECRET_KEY"] = "secret" # for WTF-forms and login

# extensions
engine = create_engine('sqlite:///tmp/blog.db')
sql_storage = SQLAStorage(engine)
blog_engine = BloggingEngine(app, sql_storage, url_prefix="/blog")
login_manager = LoginManager(app)

# user class for providing authentication
class User(UserMixin):
    def __init__(self, user_id):
        self.id = user_id

    def get_name(self):
        return "Paul Dirac" # typically the user's name

@login_manager.user_loader
@blog_engine.user_loader
def load_user(user_id):
    return User(user_id)

index_template = """
<!DOCTYPE html>
<html>
    <head> </head>
    <body>
        {%
            if current_user.is_authenticated() %}
                <a href="/logout/">Logout</a>
        {% else %}
                <a href="/login/">Login</a>
        {% endif %}
        &nbsp;&nbsp;<a href="/blog/">Blog</a>
        &nbsp;&nbsp;<a href="/blog/sitemap.xml">Sitemap</a>
        &nbsp;&nbsp;<a href="/blog/feeds/all.atom.xml">ATOM</a>
    </body>
</html>

```

```
"""

@app.route("/")
def index():
    return render_template_string(index_template)

@app.route("/login/")
def login():
    user = User("testuser")
    login_user(user)
    return redirect("/blog")

@app.route("/logout/")
def logout():
    logout_user()
    return redirect("/")

if __name__ == "__main__":
    app.run(debug=True, port=8000, use_reloader=True)
```

The key components required to get the blog hooked is explained below.

Configuring your Application

The `BloggingEngine` class is the gateway to configure blogging support to your web app. You should create the `BloggingEngine` instance like this:

```
blogging_engine = BloggingEngine()
```

You also need to pick the storage for blog. That can be done as:

```
from sqlalchemy import create_engine

engine = create_engine("sqlite:///tmp/sqlite.db")
storage = SQLAStorage(engine)
```

Once you have created the blogging engine and the storage, you can connect with your app using the `init_app` method as shown below:

```
blogging_engine.init_app(app, storage)
```

Flask-Blogging lets the developer pick the authentication that is suitable, and hence requires her to provide a way to load user information. You will need to provide a `BloggingEngine.user_loader` callback. This callback is used to load the user from the `user_id` that is stored for each blog post. Just as in Flask-Login, it should take the `unicode user_id` of a user, and return the corresponding user object. For example:

```
@blogging_engine.user_loader
def load_user(userid):
    return User.get(userid)
```

For the blog to have a readable display name, the `User` class must implement either the `get_name` method or the `__str__` method.

The `BloggingEngine` accepts an optional `config dict` argument which is passed to all the views. The keys that are currently supported include:

SITENAME	The name of the blog to be used as the brand name (default “Flask-Blogging”)
SITEURL	The url of the site.
RENDER_TEXT	Boolean value to specify if the raw text should be rendered or not. (default True)
DISQUS_SITENAME	Disqus sitename for comments (default None)
GOOGLE_ANALYTICS	Google analytics code for usage tracking (default None)

The `BloggingEngine` accepts an optional `extensions` argument. This is a list of Markdown extensions objects to be used during the markdown processing step.

Blog Views

There are various views that are exposed through Flask-Blogging. If the `url_prefix` argument in the `BloggingEngine` is `/blog`, then the URL for the various views are:

- `/blog/` (GET): The index blog posts with the first page of articles.
- `/blog/page/<post_id>/<optional slug>/` (GET): The blog post corresponding to the `post_id` is retrieved.
- `/blog/tag/<tag_name>/` (GET): The list of blog posts corresponding to `tag_name` is returned.
- `/blog/author/<user_id>/` (GET): The list of blog posts written by the author `user_id` is returned.
- `/blog/editor/` (GET, POST): The blog editor is shown. This view needs authentication.
- `/blog/delete/<post_id>/` (POST): The blog post given by `post_id` is deleted. This view needs authentication.
- `/blog/sitemap.xml` (GET): The sitemap with a link to all the posts is returned.

The view can be easily customised by the user by overriding with their own templates. The template pages that need to be customized are:

- `blog/index.html`: The blog index page used to serve index of posts, posts by tag, and posts by author
- `blog/editor.html`: The blog editor page.
- `blog/page.html`: The page that shows the given article.
- `blog/sitemap.xml`: The sitemap for the blog posts.

Screenshots

4.1 Blog Page

Delete Edit New

Dirac Equation

Posted by [Paul Dirac](#) on 03 Jun, 2015

In particle physics, the Dirac equation is a relativistic wave equation derived by British physicist Paul Dirac in 1928. In its free form, or including electromagnetic interactions, it describes all spin-1/2 massive particles, for which parity is a symmetry, such as electrons and quarks, and is consistent with both the principles of quantum mechanics and the theory of special relativity.[1] and was the first theory to account fully for special relativity in the context of quantum mechanics.

Dirac's Equation is given as:

$$(\beta mc^2 + c(\alpha_1 p_1 + \alpha_2 p_2 + \alpha_3 p_3)) \psi(x, t) = i\hbar \frac{\partial \psi(x, t)}{\partial t}$$

 PHYSICS

0 Comments	test	Gouthaman Balar...
 Recommend	 Share	Sort by Best ▾


 Start the discussion...

Be the first to comment.

4.2 Blog Editor

API Documentation

5.1 Module contents

Flask-Blogging is a Flask extension to add blog support to your web application. This extension uses Markdown to store and then render the webpage.

Author: Gouthaman Balaraman

Date: June 1, 2015

5.2 Submodules

5.3 flask_blogging.engine module

The BloggingEngine module.

```
class flask_blogging.engine.BloggingEngine(app=None, storage=None, url_prefix=None,
                                         post_processor=None, config=None, extensions=None)
```

Bases: object

The BloggingEngine is the class for initializing the blog support for your web app. Here is an example usage:

```
from flask import Flask
from flask.ext.blogging import BloggingEngine, SQLAStorage
from sqlalchemy import create_engine

app = Flask(__name__)
db_engine = create_engine("sqlite:///tmp/sqlite.db")
storage = SQLAStorage(db_engine)
blog_engine = BloggingEngine(app, storage)
```

```
__init__(app=None, storage=None, url_prefix=None, post_processor=None, config=None, extensions=None)
```

Parameters

- **app** (*object*) – Optional app to use
- **storage** (*object*) – The blog storage instance that implements the Storage class interface.
- **url_prefix** (*str*) – (optional) The prefix for the URL of blog posts (default None)

- **post_processor** (*object*) – (optional) The post processor object. If none provided, the default is used.
- **config** (*dict*) – (optional) A dictionary of config values. See docs for the keys that can be specified.
- **extensions** (*list*) – A list of markdown extensions to add to post processing step.

Returns

init_app (*app, storage*)
Initialize the engine.

Parameters

- **app** – The app to use
- **storage** – The blog storage instance that implements the Storage class interface.

user_loader (*callback*)

The decorator for loading the user.

Parameters **callback** – The callback function that can load a user given a unicode user_id.

Returns The callback function

5.4 flask_blogging.processor module

```
class flask_blogging.processor.PostProcessor
Bases: object

classmethod all_extensions()

classmethod construct_url(post)
static create_slug(title)
classmethod custom_process(post)
    Override this method to add additional processes. The result is that the post dict is modified or enhanced
    with newer key value pairs.

    Parameters post (dict) – The post data with values for keys such as title, text, tags etc.

classmethod process(post, render=True)
    This method takes the post data and renders it :param post: :param render: :return:

classmethod render_text(post)
classmethod set_custom_extensions(extensions)
```

5.5 flask_blogging.sqlastorage module

```
class flask_blogging.sqlastorage.SQLAStorage(engine, table_prefix='')
Bases: flask_blogging.storage.Storage

The SQLAStorage implements the interface specified by the Storage class. This class uses SQLAlchemy
to implement storage and retrieval of data from any of the databases supported by SQLAlchemy. This

__init__(engine, table_prefix='')
    The constructor for the SQLAStorage class.
```

Parameters

- **engine** (*object*) – The SQLAlchemy engine instance created by calling `create_engine`. One can also use Flask-SQLAlchemy, and pass the engine property.
- **table_prefix** (*str*) – (Optional) Prefix to use for the tables created (default "").

count_posts (*tag=None, user_id=None, include_draft=False*)

Returns the total number of posts for the give filter

Parameters

- **tag** (*str*) – Filter by a specific tag
- **user_id** (*str*) – Filter by a specific user
- **include_draft** (*bool*) – Whether to include posts marked as draft or not

Returns The number of posts for the given filter.

delete_post (*post_id*)

Delete the post defined by `post_id`

Parameters **post_id** (*int*) – The identifier corresponding to a post

Returns Returns True if the post was successfully deleted and False otherwise.

get_post_by_id (*post_id*)

Fetch the blog post given by `post_id`

Parameters **post_id** (*int*) – The post identifier for the blog post

Returns If the `post_id` is valid, the post data is retrieved, else returns None.

get_posts (*count=10, offset=0, recent=True, tag=None, user_id=None, include_draft=False*)

Get posts given by filter criteria

Parameters

- **count** (*int*) – The number of posts to retrieve (default 10)
- **offset** (*int*) – The number of posts to offset (default 0)
- **recent** (*bool*) – Order by recent posts or not
- **tag** (*str*) – Filter by a specific tag
- **user_id** (*str*) – Filter by a specific user
- **include_draft** (*bool*) – Whether to include posts marked as draft or not

Returns A list of posts, with each element a dict containing values for the following keys: (title, text, draft, post_date, last_modified_date). If count is `None`, then all the posts are returned.

save_post (*title, text, user_id, tags, draft=False, post_id=None*)

Persist the blog post data. If `post_id` is `None` or `post_id` is invalid, the post must be inserted into the storage. If `post_id` is a valid id, then the data must be updated.

Parameters

- **title** (*str*) – The title of the blog post
- **text** (*str*) – The text of the blog post
- **user_id** (*str*) – The user identifier
- **tags** (*list*) – A list of tags

- **draft** (*bool*) – (Optional) If the post is a draft or needs to be published. (default False)
- **post_id** (*int*) – (Optional) The post identifier. This should be None for an insert call, and a valid value for update. (default None)

Returns The post_id value, in case of a successful insert or update. Return None if there were errors.

5.6 flask_blogging.storage module

```
class flask_blogging.storage.Storage
```

Bases: object

```
count_posts (tag=None, user_id=None, include_draft=False)
```

Returns the total number of posts for the given filter

Parameters

- **tag** (*str*) – Filter by a specific tag
- **user_id** (*str*) – Filter by a specific user
- **include_draft** (*bool*) – Whether to include posts marked as draft or not

Returns The number of posts for the given filter.

```
delete_post (post_id)
```

Delete the post defined by post_id

Parameters **post_id** (*int*) – The identifier corresponding to a post

Returns Returns True if the post was successfully deleted and False otherwise.

```
get_post_by_id (post_id)
```

Fetch the blog post given by post_id

Parameters **post_id** (*int*) – The post identifier for the blog post

Returns If the post_id is valid, the post data is retrieved, else returns None.

```
get_posts (count=10, offset=0, recent=True, tag=None, user_id=None, include_draft=False)
```

Get posts given by filter criteria

Parameters

- **count** (*int*) – The number of posts to retrieve (default 10). If count is None, all posts are returned.
- **offset** (*int*) – The number of posts to offset (default 0)
- **recent** (*bool*) – Order by recent posts or not
- **tag** (*str*) – Filter by a specific tag
- **user_id** (*str*) – Filter by a specific user
- **include_draft** (*bool*) – Whether to include posts marked as draft or not

Returns A list of posts, with each element a dict containing values for the following keys: (title, text, draft, post_date, last_modified_date). If count is None, then all the posts are returned.

```
static normalize_tags (tags)
```

save_post (*title, text, user_id, tags, draft=False, post_id=None*)

Persist the blog post data. If *post_id* is `None` or *post_id* is invalid, the post must be inserted into the storage. If *post_id* is a valid id, then the data must be updated.

Parameters

- **title** (*str*) – The title of the blog post
- **text** (*str*) – The text of the blog post
- **user_id** (*str*) – The user identifier
- **tags** (*list*) – A list of tags
- **draft** (*bool*) – If the post is a draft or if needs to be published.
- **post_id** (*int*) – The post identifier. This should be `None` for an insert call, and a valid value for update.

Returns The *post_id* value, in case of a successful insert or update. Return `None` if there were errors.

5.7 flask_blogging.views module

`flask_blogging.views.delete(*args, **kwargs)`

`flask_blogging.views.editor(*args, **kwargs)`

`flask_blogging.views.index(count, page)`

Serves the page with a list of blog posts

Parameters

- **count** –
- **offset** –

Returns

`flask_blogging.views.page_by_id(post_id, slug)`

`flask_blogging.views.posts_by_author(user_id, count, page)`

`flask_blogging.views.posts_by_tag(tag, count, page)`

`flask_blogging.views.recent_feed()`

`flask_blogging.views.sitemap()`

5.8 flask_blogging.forms module

```
class flask_blogging.forms.BlogEditor(formdata=<class 'flask_wtf.form._Auto'>, obj=None,
                                      prefix=' ', csrf_context=None, secret_key=None,
                                      csrf_enabled=None, *args, **kwargs)
```

`draft = <UnboundField(BooleanField, ('draft'), {'default': False})>`

`submit = <UnboundField(SubmitField, ('submit'), {})>`

`tags = <UnboundField(StringField, ('tags'), {'validators': [<wtforms.validators.DataRequired object at 0x7fe37fd5ac90>]}`

`text = <UnboundField(TextAreaField, ('text'), {'validators': [<wtforms.validators.DataRequired object at 0x7fe37fd5ac90>]}`

```
title = <UnboundField(StringField, ('title'), {'validators': [<wtforms.validators.DataRequired object at 0x7fe37fd5ab9]})>
```

f

flask_bloggin, 11
flask_bloggin.engine, 11
flask_bloggin.forms, 15
flask_bloggin.sqlastorage, 12
flask_bloggin.storage, 14
flask_bloggin.views, 15

Symbols

`__init__()` (flask_blogging.engine.BloggingEngine method), 11
`__init__()` (flask_blogging.sqlstorage.SQLAStorage method), 12

A

`all_extensions()` (flask_blogging.processor.PostProcessor class method), 12

B

`BlogEditor` (class in flask_blogging.forms), 15
`BloggingEngine` (class in flask_blogging.engine), 11

C

`construct_url()` (flask_blogging.processor.PostProcessor class method), 12
`count_posts()` (flask_blogging.sqlstorage.SQLAStorage method), 13
`count_posts()` (flask_blogging.storage.Storage method), 14
`create_slug()` (flask_blogging.processor.PostProcessor static method), 12
`custom_process()` (flask_blogging.processor.PostProcessor class method), 12

D

`delete()` (in module flask_blogging.views), 15
`delete_post()` (flask_blogging.sqlstorage.SQLAStorage method), 13
`delete_post()` (flask_blogging.storage.Storage method), 14

`draft` (flask_blogging.forms.BlogEditor attribute), 15

E

`editor()` (in module flask_blogging.views), 15

F

`flask_blogging` (module), 11
`flask_blogging.engine` (module), 11

`flask_blogging.forms` (module), 15
`flask_blogging.sqlstorage` (module), 12
`flask_blogging.storage` (module), 14
`flask_blogging.views` (module), 15

G

`get_post_by_id()` (flask_blogging.sqlstorage.SQLAStorage method), 13
`get_post_by_id()` (flask_blogging.storage.Storage method), 14
`get_posts()` (flask_blogging.sqlstorage.SQLAStorage method), 13
`get_posts()` (flask_blogging.storage.Storage method), 14

I

`index()` (in module flask_blogging.views), 15
`init_app()` (flask_blogging.engine.BloggingEngine method), 12

N

`normalize_tags()` (flask_blogging.storage.Storage static method), 14

P

`page_by_id()` (in module flask_blogging.views), 15
`PostProcessor` (class in flask_blogging.processor), 12
`posts_by_author()` (in module flask_blogging.views), 15
`posts_by_tag()` (in module flask_blogging.views), 15
`process()` (flask_blogging.processor.PostProcessor class method), 12

R

`recent_feed()` (in module flask_blogging.views), 15
`render_text()` (flask_blogging.processor.PostProcessor class method), 12

S

`save_post()` (flask_blogging.sqlstorage.SQLAStorage method), 13
`save_post()` (flask_blogging.storage.Storage method), 14

set_custom_extensions() (flask_blogging.processor.PostProcessor
 class method), [12](#)
sitemap() (in module flask_blogging.views), [15](#)
SQLAStorage (class in flask_blogging.sqlastorage), [12](#)
Storage (class in flask_blogging.storage), [14](#)
submit (flask_blogging.forms.BlogEditor attribute), [15](#)

T

tags (flask_blogging.forms.BlogEditor attribute), [15](#)
text (flask_blogging.forms.BlogEditor attribute), [15](#)
title (flask_blogging.forms.BlogEditor attribute), [15](#)

U

user_loader() (flask_blogging.engine.BloggingEngine
 method), [12](#)